



ZEISS Touit lenses

Autofocus lenses for Sony NEX
and Fujifilm X cameras.



We make it visible.

The moment a lens
makes your camera perfect.
This is the moment we work for.

// PERFECTION
MADE BY ZEISS

Bringing together what belongs together.

Discover our brand new range of Touit® lenses and experience the level of performance ZEISS quality can help you unleash in mirrorless cameras like the Sony NEX or Fujifilm X.





GENERAL PRODUCT FEATURES

Touit lenses from ZEISS are substantially smaller and lighter than comparable SLR lenses. This makes for a lightweight, more compact kit when combined with mirrorless system cameras, and allows you to take exceptionally high-quality photos in just about any situation and at any time.



product
design award

2013



reddot design award
winner 2013

Outstanding image quality

- Excellent reflection reduction thanks to ZEISS T*[®] anti-reflective coating
- Advanced stray light reduction
- Virtually circular aperture with 9 blades for especially harmonious rendition of highlights outside the focal plane

High precision

- Precise, durable and low-weight mechanical parts
- Complete compatibility with all Sony NEX and Fujifilm X camera functions (including reliable autofocus)

High-quality workmanship

- Robust metal design for many years of use
- Grippy focus ring for precise manual focussing
- Innovative product design for ease of use and maximum aesthetic demands

ZEISS Touit lenses come standard with a matching lens shade.



Photo: David Maupilé


TOUIT 2.8/12



As far as the eye can see: the combination of one of the most extreme angles with an APS-C sensor, superior imaging performance and light weight makes taking wide-angle shots with this lens even more enjoyable.

Design

- Distagon with 11 lens elements in 8 groups
- Lens with aspheric optical surface
- Lens made of special glass with anomalous partial dispersion
- Floating elements design



Specifications

Focal length	12 mm
Aperture range	f/2.8–f/22
Elements/groups	11/8
Focusing range m/ft	0.18 – ∞/0.59 – ∞
Field angle* (diag./horiz./vert.)	99/89/66°
Coverage** (cm/inch)	22 x 14.4/8.66 x 5.67

*Based on APS-C format. **At close range.




Photo: Laura Saffioti


TOUIT 1.8/32



Magician of the moment: a compact standard focal length lens specially designed for compact system cameras such as the Sony NEX and Fujifilm X. Spontaneously capturing special moments in perfect quality just got a whole lot easier.

Design

- Planar with 8 lens elements in 5 groups



Specifications

Focal length	32 mm
Aperture range	f/1.8–f/22
Elements/groups	8/5
Focusing range m/ft	0.37 – ∞/1.21 – ∞
Field angle* (diag./horiz./vert.)	48/40/29°
Coverage** cm/inch	21.4 x 14.2/8.43 x 5.59

*Based on APS-C format. **At close range.





Photo: Dr. Michael Pollmann

TOUIT 2.8/50M



Design

- Makro Planar with 14 lens elements in 11 groups
- Lens with aspheric optical surface
- Lens made of special glass with anomalous partial dispersion
- Floating elements design



A perfectionist with an eye for the details: with its exceptional image performance up to a scale of 1:1, this macro lens is the ideal choice for extreme close-ups. But it also comes into its own when shooting portraits or panoramas as a light tele-lens.

Specifications

Focal length	50 mm
Aperture range	f/2.8–f/22
Elements/groups	14/11
Focusing range m/ft	0.15 – ∞/0.49 – ∞
Field angle* (diag./horiz./vert.)	31/26/18°
Coverage** cm/inch	23.5 x 15.6/9.25 x 6.14

*Based on APS-C format. **At close range.

Carl Zeiss T*

ACCESSORIES



ZEISS T* UV filters and POL filters (circular)

These filters featuring the ZEISS T* anti-reflective coating optimally protect your front lens. The UV filters give your pictures more brilliance; the POL filters reduce reflections on nonmetallic surfaces and increase color saturation.

- High fitting accuracy for fast filter change
- Can be used with a lens shade
- Available in all standard sizes



ZEISS Air Cell comfort straps

These camera straps minimize shoulder and neck strain, even with heavy equipment.

- High degree of wearing comfort with Air Cell padding
- Strap length adjustable at both ends



ZEISS lens cleaning kit

This lens cleaning kit is designed for use with multi-coated camera lenses. The cleaning kit is packed in a fabric belt bag and contains:

- Lens cleaning agent
- Dust brush
- Microfibre cloth
- 10 moistened cleaning cloths
- User manual for professional lens care



SPECIFICATIONS

	Length* mm/inch	Diameter* mm/inch (max.)	Weight* g/oz.	Filter thread	E	X
Super wide angle						
Touit 2.8/12	81–86/3.19–3.39	82/3.23	260–270/9.12–9.6	M 67 x 0.75	■	■
Standard						
Touit 1.8/32	72–76/2.83–2.99	65/2.56	200–210/7.04–7.36	M 52 x 0.75	■	■
Macro						
Touit 2.8/50M	104–108/4.09–4.25	65/2.95	290/10.24	M 52 x 0.75	■	■

*Dimensions and weight may vary according to the camera mount.

You can find further information the specifications and compatibility at

www.zeiss.com/photo



SHARE YOUR FASCINATION



Photo: community member Mac Kwan/Touit 2.8/12



Better together: visit ZEISS on the Internet to keep in contact with other photographers, exchange tips and tricks, and get regular news updates. You can find a large community of photographers and videographers from all over the world on our blog, Facebook, Twitter, Flickr and Vimeo.



zeiss.com/photo



zeiss.com/clnblog



facebook.com/carlzeisslenses



twitter.com/carlzeisslenses



flickr.com/groups/carlzeisslenses



vimeo.com/groups/carlzeisslenses

Carl Zeiss AG
Camera Lens Division
73446 Oberkochen
Germany

Phone: +49 7364 20-6175
Fax: +49 7364 20-4045
Email: photo@zeiss.de

www.zeiss.com/photo

EN_10_025_150II Printed in Germany ZIG-CZ-I/2014 Noo
Subject to change in design and scope of delivery as a result of ongoing technical development.