COMPARE THE NEW CONTENDERS IN SUPER TELEPHOTO

Which of our flagship telephoto lenses are right for you?

Compare the 150-600mm F5-6.3 DG OS HSM | S and the 150-600mm F5-6.3 DG OS HSM | C.



2 LENSES WITH AWARD-WINNING PEDIGREE & SHARED DNA

New Optical Stabilizer: Accelerometer for vertical or horizontal panning

Dust & Splash-Proof Mount

New Zoom Lock: Lock zoom ring at any focal length for stable shooting
USB Dock & Teleconverter compatible
Sigma, Canon & Nikon mount compatible
Qualifies for Mount Conversion Service
USB Dock Compatible

SIGMA 150-600MM F5-6.3 DG OS HSM WHAT'S THE RIGHT CHOICE FOR YOU?



A hyper-telephoto zoom optimized for professional use.





Outstanding optical performance in a lightweight package.



Sports		Contemporary
150-600mm	FOCAL RANGE	150-600mm
4.8x11.4 in.	DIMENSION	4.1x10.2 in.
24 Elements in 16 Groups 2 FLD and 3 SLD	GLASS	20 Elements in 14 Groups 1 FLD and 3 SLD
6.3lbs	WEIGHT	4.3lbs
105mm	FILTER SIZE	95mm
Construction	DUST/SPLASH PROOF	Mount
Front & Rear	WATER/OIL REPELLENT COATING	Rear Element
Metal	LENS HOOD	Plastic
Non-Removable Three 1/4" sockets Shoulder Strap Clicks into position every 90° Optional TS-81 compatible with Arca-Swiss quick release plates; includes 1/4" and 3/8" sockets	TRIPOD SOCKET	Removable One 1/4" socket Shoulder Strap Protective cover slides over collar mounting bolts for improved hand- holding feel
9 (Rounded diaphragm)	NUMBER OF DIAPHRAGM BLADES	9 (Rounded diaphragm)

F22	MINIMUM APERTURE	F22
2.6m	MINIMUM FOCUSING DISTANCE	2.8m
1:5	MAXIMUM MAGNIFICATION RATIO	1:4:9
95.3mm	ZOOM RING DIAMETER	88.2mm
Yes	FOCUS LIMITER	Yes
Available	FULL-TIME MANUAL MODE	Available
Available	MOUNT CONVERSION SERVICE	Available
Available	MO (MANUAL OVERRIDE)	Available
Yes	RUBBER SEALING MOUNT PROTECTOR	Yes
Yes	BRASS BAYONET MOUNT	Yes
Rotate / Push-Pull	ZOOM OPERATION	Rotate
Included	CASE	Included